



ASSEMBLY INSTRUCTION

ITEM# 60162

- 1. Thread nipple into center hole of mounting strip about 4 complete turns. Lock in place with washer and hex nut.
This nipple should extend long enough to protrud through the canopy when it is mounted.
 - 2. Fasten mounting strip onto wall outlet box using two outlet box screws.
 - 3. Connect the wires from the fixture to the power supply wires from outlet box.
 - A. Twist together white wire from the fixture with white wire from outlet box. Cover with wire connector.
 - B. Twist together black wire from the fixture with black wire from outlet box. Cover with wire connector.
 - C. Wrap the ground wires from fixture and the outlet box around the ground screw located on the mounting strip.
Tighten the green ground screw to the mounting strip.
 - 4. Pass the bracket through the nipple. Screw cap nut onto the nipple on the mounting strip until the fixture body is held firmly to the wall.
 - 5. Install the bulb (not included) into socket. Do not use greater than 60-watt bulb.
 - 6. Thread 5/32" nipple into strip on the bracket.
 - 7. Carefully unpack the glass from box,Set the glass over 5/32" nipple, and secure by tightenting with ball nut.
- NOTE:** Carefully remove the fixture from the carton. Check that all parts shown in package parts 1 and parts 2 are included.
Be carefully not to misplace any of the screws or wire connectors, which are needed for installing the fixture.

PACKAGE PART

Wire connector	2	Cap Nut	1
Green ground screw	1	Ball Nut	2
Outlet box screw	2	5/32" NIPPLE	2
Mounting strip	1	Glass	1
3/8" Nut	1		
3/8" Nipple	1		
Washer	1		

